

## **BLANK PAGE**



IS: 3176 - 1983

## Indian Standard

REAFFIRMED

2006

# SPECIFICATION FOR TOP ROLLERS FOR RING AND SPEED FRAMES

(Second Revisión)

UDC 677.052.948.4



@ Copyright 1983

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARQ NEW DELHI 110002

## AMENDMENT NO. 2 DECEMBER 1985

TO

# IS: 3176-1983 SPECIFICATION FOR TOP ROLLERS FOR RING AND SPEED FRAMES

## (Second Revision)

( Page 3, clause 0.2, line 2) — Delete the words 'and without'.

( Page 3, clause 1.1 ) — Delete the words 'fixed boss type'.

( Page 3, clause 1.1.1) — Add the following new clauses and renumber the subsequent clauses accordingly:

### '2. TYPES

2.1 The top rollers shall be any of the following two types:

Type 1 — Fixed boss type ( see Fig. 1 ).

Type 2 — Loose boss type with non-removable (non-detachable) shell (see Fig. 2).




Fig. 2 A Typical Loose Boss Type Roller with Non-Removable (Non-Detachable) Shell

( Page 3, clause 2.1 ) — Add the words ' or Fig. 2 ' at the end of the sentence.

( Page 5, clause 4.2.1 ) - Substitute 'Fig. 3' for 'Fig. 2'.

( Page 6, Fig. 2) - Renumber as 'Fig. 3'.

( TDC 30 )



## AMENDMENT NO. 1 NOVEMBER 1984

TO

## IS:3176-1983 SPECIFICATION FOR TOP ROLLERS FOR RING AND SPEED FRAMES

(Second Revision)

## Alteration

(Page 4, Note under clause 3.3) - Delete.

(TDC 30)

Reprography Unit, ISI, New Delhi, India

## Indian Standard

# SPECIFICATION FOR TOP ROLLERS FOR RING AND SPEED FRAMES

## (Second Revision)

Spinning Machinery (Cotton System) Sectional Committee, TDC 30

Chairman

SHRI SURESH M. MEHTA

Representing

Association of Merchants & Manufacturers of Textile Stores & Machinery (India), Bombay

Members

SHRIJ. C. AGRAWAL

DR N. BALASUBRAMANIAN

SHRI D. B. BARAT

SHRI G. B. SATHE (Alternate)

DR S. K. BHATIA

SHRI V. K. MITTAL (Alternate)
SHRI G. M. BHATTACHARYA

SHRI T. K. SEN (Alternate)
SHRI S. GOVINDARAJAN

SHRI A. K. GUPTA

SHRI A. K. AGRAWAL ( Alternate )

SHRI P. S. JAIN SHRI V. B. PATIL GAYAKWAR

(Alternate)

SHRI D. JAYAVARTHANAVELU

SHRI K. B. KRISHNAN ( Alternate ) SHRI K. S. KELKAR

SHRI K. N. PESHOTAN ( Alternate )

Textile Machinery Manufacturers' Association

(India), Bombay

The Bombay Textile Research Association, Bombay

B. R. T. Limited, Bombay

National Textile Corporation Ltd, New Delhi

Machinery Manufacturers Corporation Ltd, Calcutta

The South India Textile Research Association,

Coimbatore
Ahmedabad Textile Industry's Research Association, Ahmadabad

The Textile Association (India) Regd, Bombay

Lakshmi Machine Works Ltd, Coimbatore

The Bombay Dyeing & Manufacturing Co Ltd,
Bombay

(Continued on page 2)

## Copyright 1983

#### INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

#### IS: 3176 - 1983

#### (Continued from page 1)

#### Members

SHRI D. LAKSHMINARAYANASWAMY The

SHRI A. T. MERCHANT SHRI N. B. MISTRY

SHRI S. S. NERURKAR SHRI A. M. DOSHI ( Alternate )

SHRI MOHAN PURANDARE

SHRI N. RADHAKRISHNAN SHRI P. T. SHASTRI ( Alternate )

SHRI K. R. RAGRINA SHRI B. S. RAJ

SHRI A. K. HALDER ( Alternate)

REPRESENTATIVE REPRESENTATIVE

SHRI T. A. SHANMUGANATHAN

SHRI R. L. KUMAR ( Alternate ) SHRI S. G. SHEVADE

SHRI S. G. MISTRY ( Alternate )

DR T. V. K. SRIVASTAVA SHRI S. P. GHOSAL (Alternate)

Shri M. N. Ved Prof S. G. Vinzanekab

PROF A. A. GUPTE ( Alternate ) SHRI G. VISWANATHAN SHRI S. M. CHARRABORTY,

Director (Tex)

### Representing

India Southern Mills' Association. Coimbatore

The Finlay Mills Ltd, Bombay

Lakshmiratan Engineering Works Ltd. Bombay Textiles Committee, Bombay

The Ahmedabad Textile Mills' Association. Ahmadabad

The Khatau Makanji Spg & Wvg Co Ltd, Bombay

The Bombay Millowners' Association, Bombay Texmaco Limited, Calcutta

The Delhi Cloth & General Mills Co Ltd, Delhi The Standard Mills Co Ltd, Bombay Textool Company Limited, Coimbatore

Mafatlal Engineering Industries Ltd, Bombay

Office of the Textile Commissioner, Bombay

The Century Spg & Mfg Co Ltd, Bombay Victoria Jubilee Technical Institute, Bombay

Binny Limited, Madras Director General, ISI (Ex-officio Member)

Secretary SHBI R. K. DUA Deputy Director ( Tex ), ISI

## Indian Standard

# SPECIFICATION FOR TOP ROLLERS FOR RING AND SPEED FRAMES

## (Second Revision)

## O. FOREWORD

- **6.1** This Indian Standard (Second Revision) was adopted by the Indian Standards Institution on 31 March 1983, after the draft finalized by the Spinning Machinery (Cotton System) Sectional Committee had been approved by the Textile Division Council.
- 0.2 This standard was published in 1965 and subsequently revised in 1971. In this second revision, loose boss type rollers with and without removable shells have been excluded as these types of top rollers are not in use now. This opportunity has also been taken to modify the requirements for the material for manufacture of arbors and shells with raceways.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

### 1. SCOPE

- 1.1 This standard specifies requirements for fixed boss type antifriction bearing top rollers for use in ring spinning and speed frames.
- 1.1.1 This standard does not lay down requirements for bearings used in conjunction with the top rollers and cots used as covering.

#### 2. NOMENCLATURE

2.1 For the purpose of this standard, the nomenclature of the components of the rollers shall be as indicated in Fig. 1.

<sup>\*</sup>Rules for rounding off numerical values ( revised ).




FIG. 1 A TYPICAL FIXED BOSS TYPE ROLLER

#### 3. MANUFACTURE

- 3.1 Material The arbors and shells with raceways shall be manufactured from high carbon-chromium steel conforming to Designation 103Cr2 of IS: 4398-1972\* or its equivalent.
- 3.2 Roller Gauge The roller gauge (standard centre-to-centre distance of the two bosses of top roller) should suit the spindle gauge (see IS: 5938 1970†).
- 3.3 Load-Bearing Capacity The load-bearing capacity of the top rollers shall be in line with the drafting system.

Note - The manufacturer should specify the load-bearing capacity of the rollers.

3.4 Finish — The outer surface of the shells of the rollers shall be suitably prepared to facilitate their covering with synthetic cots.

Note — Grooves, if provided, shall have depth as agreed to between the buyer and the seller.

3.5 Freedom from Defects — The top rollers shall be free from any trace of dirt, scale and rust and manufacturing defects.

## 4. REQUIREMENTS

**4.1 Diameter** — Both the shells of the top rollers shall have the same diameter as agreed to between the buyer and the seller. However, tolerance of  $^{+\ 0}_{-\ 0.05}$  mm on the agreed diameter shall be permissible.

<sup>\*</sup>Specification for carbon-chromium steel for the manufacture of balls, rollers and bearing races (first revision).

<sup>†</sup>Spindle gauges for cotton ring spinning and ring doubling (twisting) frames.

- 4.1.1 The diameter of the shells shall be measured with suitable callipers measuring to an accuracy of 0.01 mm.
- 4.2 Run-out (Total Indicator Reading) The run-out of the top rollers with covering shall be not more than 0.06 mm (TIR) and without covering (only for apron top roller) not more than 0.05 mm (TIR).
- **4.2.1** The run-out of the top rollers shall be measured with suitable dial indicators, by clamping the arbor fast on an inclined surface (see Fig. 2). The contact point of the dial indicator shall be with steel/carbide/ruby ball, to avoid penetration into the covering.

#### 5. DESIGNATION

5.1 The top rollers shall be designated as under:

Roller gauge in mm  $\times$  bare roller diameter in mm  $\times$  length of the shell in mm

### Example:

 $^{\prime}$  65  $\times$  19  $\times$  33  $^{\prime}$  will indicate 65 mm roller gauge, 19 mm bare roller diameter and 33 mm length of the shell.

#### 6. LUBRICATION AND PACKING

- 6.1 The top rollers shall be suitably greased and given a thin coat of rust-preventive oil all over taking care that the oil does not penetrate the bearing. The top rollers with cots shall be greased only at the sides.
- 6.2 The top rollers shall thereafter be wrapped in wax-coated paper or put in polyethylene bags. An appropriate number of the rollers shall then be packed in a suitable container.

#### 7. MARKING

- 7.1 Each container of the top rollers shall be marked with the following:
  - a) Manufacturer's name, initials or trade-mark, if any;
  - b) Designation of the top rollers;
  - c) Number of top rollers in the container; and
  - d) Lot/batch number.

Note—To facilitate distinction of top rollers manufactured by different manufacturers, every manufacturer should ensure that the top rollers manufactured by him are distinguishable.




Fig. 2 A TYPICAL ARRANGEMENT FOR MEASURING RUN-OUT OF TOP ROLLER

7.1.1 The containers may also be marked with the ISI Certification Mark.

Note—The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

## INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

## Base Units

QUANTITY	Unit	Symbol	
Length	metre	m	
Mass	kilogram	kg	
Time	second		
Electric current	ampere	A	
Thermodynamic temperature	kelvin	ĸ	
Luminous intensity	candel <b>a</b>	cd	
Amount of substance	mole	mol	
Supplementary Units			
QUANTITY	Unit	SYMBOL	
Plane angle	radian	rad	
Solid angle	steradian	sr	
Derived Units			
QUANTITY	Unit	SYMBOL	DEFINITION
Force	newton	N	$1 N = 1 \text{ kg.m/s}^2$
Energy	joule	J	1 J = 1 N.m
Power	watt	w	1  W = 1  J/s
Flux	weber	Wb	1  Wb = 1  V.s
Flux density	tesla	T	$1 \text{ T} \cdot = 1 \text{ Wb/m}^2$
Frequency	hertz	Hz	1  Hz = 1  c/s (s-1)
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	v	1 V = 1 W/A
Pressure, stress	pascal	Pa	$1 Pa = 1 N/m^2$

# PUBLICATIONS OF INDIAN STANDARDS INSTITUTION INDIAN STANDARDS

Over 10 000 Indian Standards covering various subjects have been issued so far. Of these, the standards belonging to the Textile Group fall under the following categories:

Aeronautical textiles Chemical test methods Colour fastness of textile materials Cotton fabrics - handloom, khadi, and mill-made Dvestuffs Grading of fibres and yarns Grading of raw silk Hosiery Jute - bags and fabrics Jute mill accessories Narrow fabrics National flag of India Nylon fabrics Packaging codes Physical test metods

Rayon fabrics

Rayon fabrics, handloom Ropes and Cordages Sampling of textiles, methods for Slik fabrics — handloom and Khadi Sizing and finishing materials Spinning machinery components Terminology Textile floor coverings Textile maferials for fishing Textile mill accessories (other than jute mills) Twines Weaving machinery components Wool fabrics - handloom, khadi. and mill-made Yarn and similar structures Unclassified

#### INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 26 60 21, 27 01 31 Regional Offices:	Telegrams : Manak Te	sanstha lephone
Western : Novelty Chambers, Grant Road	BOMBAY 400007	89 65 28
Eastern : 5 Chowringhee Approach	CALCUTTA 700072	27 50 90
Southern : C. I. T. Campus	MADRAS 600113	41 24 42
Northern: B69, Phase VII, Industrial Focal Point	S.A S. NAGAR ( MOHALI ) 160051	8 78 26
Branch Offices:		
'Pushpak', Nurmohamed Shaikh Marg, Khanpur	AHMADABAD 380001	2 03 91
'F' Block, Unity Bldg, Narasimharaja Square	BANGALORE 560002	22 48 05
Gangotri Complex, Bhadbhada Road, T. T. Nagar	BHOPAL 462003	6 27 16
22E Kalpana Area	BHUBANESHWAR 751014	5 36 27
5-8-56C L. N. Gupta Marg	HYDERABAD 500001	22 10 83
R 14 Yudhister Marg, C Scheme	JAIPUR 802005	6 98 82
117/418 B Sarvodaya Nagar	KANPUR 208005	4 72 92
Patliputra Industrial Estate	PATNA 800013	6 28 08
Hantex Bidg (2nd Floor), Rly Station Road	TRIVANDRUM 695001	32 27